

ARY cable suspended

MOVE IT 25

050-0511417F



Project / Type

Notes

Count / Date



Decorative pendant light inset made of aluminium; surface white powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 1500mm suspension, incl. feed (white), can be individually shortened; shades available as accessory in RAL colours velvet beige, madeira brown, kingfisher grey, woodpecker olive, signal white or signal black; accessories are listed separately; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 44° beam; degree of protection IP20; PC3 48V; non-dimmable; light source not replaceable;



General

Ceiling , Track Suspended

white , RAL9016 ¹

IP20

1040 lm

LED

2700 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 96 , R_f: 90 , R₍₁₋₅₎: 88

MR 0.55

MDER 0.5

Optical

flood

beam angle 44°

Electrical

non DIM

14.1 W

PC3 48V

74 lm/W

Physical

cable 1500 mm


diameter 47 mm

height 110 mm

0.35 kg


¹ RAL code

Light distribution



flood 44°		
h (m)	EO° (lx)	ø (m)
1	1930	0.82
2	480	1.64
3	210	2.45
4	120	3.27
5	80	4.09

Product drawing



Installation instructions



Lighting calculator

