

w201 Extra small pendant s3 suspended

MOVE IT 25 / 25 S / 45 with hook

050-0463437



Project / Type

Notes

Count / Date



General

Ceiling | Suspended
traffic white | RAL 9016
IP20
572 lm
optical inset 96 lm/W ¹

LED

2700 K
CRI ≥ 90
L90 / 50000 h
initial MacAdam ≤ 3 SDCM

Optical

flood | beam angle 91°
PstLM ≤ 1.0 ² | SVM ≤ 0.4 ²

Electrical

DALI-2 | 1 DALI Addr.
PC3 | 48 V
fixture 7.9 W
optical inset 5.9 W

Physical


diameter 151 mm | height 51 mm
0.75 kg

¹ incl. consideration of optical losses

² Value of containing product at full load (undimmed)

Decorative pendant light inset made of aluminium; cone-shaped shade; surface traffic white powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 3500mm suspension, incl. feed (traffic white), can be individually shortened, incl. ceiling mounting ring + hook (traffic white) for multiple positioning of the luminaire in the room; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3; 48 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable; control gear replaceable by an authorized professional;


Light distribution



flood 91°

h (m)	EO° (lx)	ø (m)
1	264	2.02
2	66	4.05
3	29	6.07
4	17	8.10
5	11	10.12

Product drawing



Installation instructions



Lighting calculator

