

# w201 Extra small pendant s3 suspended

MOVE IT 25 / 25 S / 45 with hook

050-0463437



Project / Type

Notes

Count / Date



## General

Ceiling | Suspended

white | RAL 9016 <sup>1</sup>

IP20

572 lm

optical inset 96 lm/W <sup>2</sup>

## LED

2700 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

## Optical

flood | beam angle 91°

PstLM ≤ 1.0 <sup>3</sup> | SVM ≤ 0.4 <sup>3</sup>

## Electrical

DALI-2

PC3 | 48 V

fixture 7.9 W

optical inset 5.9 W

## Physical

diameter 151 mm | height 51 mm


0.75 kg

Decorative pendant light inset made of aluminium; cone-shaped shade; surface white powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 3500mm suspension, incl. feed (white), can be individually shortened, incl. ceiling mounting ring + hook (white) for multiple positioning of the luminaire in the room; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3; 48 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable; control gear replaceable by an authorized professional;

<sup>1</sup> RAL code <sup>2</sup> incl. consideration of optical losses

<sup>3</sup> Value of containing product at full load (undimmed)


## Light distribution



flood 91°

h (m)	EO° (lx)	ø (m)
1	264	2.02
2	66	4.05
3	29	6.07
4	17	8.10
5	11	10.12

## Product drawing



## Installation instructions



## Lighting calculator

