

# w201 Extra small pendant s2 suspended

MOVE IT 25 with hook

050-0462438



Project / Type

Notes

Count / Date



## General

Ceiling , Suspended

black , RAL 9005 <sup>1</sup>

IP20

520 lm

## LED

2700 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

## Optical

flood

beam angle 91°

## Electrical

DALI-2

7.9 W

PC3 350mA

66 lm/W

## Physical

diameter 91 mm


height 94 mm

0.6 kg

<sup>1</sup> RAL code

Decorative pendant light inset made of aluminium; cone-shaped shade; surface black powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 3500mm suspension, incl. feed (black), can be individually shortened, incl. ceiling mounting ring + hook (black) for multiple positioning of the luminaire in the room; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3 350mA; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable; control gear replaceable by an authorized professional;


## Light distribution



flood 91°

h (m)	EO <sup>2</sup> (lx)	ø (m)
1	246	2.02
2	61	4.04
3	27	6.07
4	15	8.09
5	10	10.11

## Product drawing



## Installation instructions



## Lighting calculator

