

w201 Extra small pendant s2 suspended

MOVE IT 25 with hook

050-0462437



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

white , RAL 9016 ¹

IP20

572 lm

LED

2700 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

Optical

flood

beam angle 91°

Electrical

DALI-2

7.9 W

PC3 350mA

72 lm/W

Physical

diameter 91 mm


height 94 mm

0.64 kg

¹ RAL code

Decorative pendant light inset made of aluminium; cone-shaped shade; surface white powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 3500mm suspension, incl. feed (white), can be individually shortened, incl. ceiling mounting ring + hook (white) for multiple positioning of the luminaire in the room; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3 350mA; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable; control gear replaceable by an authorized professional;


Light distribution



flood 91°

h (m)	EO° (lx)	ø (m)
1	264	2.02
2	66	4.05
3	29	6.07
4	17	8.10
5	11	10.12

Product drawing



Installation instructions



Lighting calculator

