

# JUST 45 MOVE IT 25 / 25 S / 45

050-0131E3XM



Project / Type

Notes

Count / Date



## General

Ceiling / Wall , Track

tilt max 90°

rotation 360°

special colours

IP20

390 lm

optical inset 45 lm/W<sup>1</sup>

## LED

colour warm dimming

2000 K - 3000 K

CRI ≥ 95

L80 / 50000 h

initial MacAdam ≤ 4 SDCM

R<sub>g</sub>: 100, R<sub>f</sub>: 91, R<sub>f(1-15)</sub>: 90

MR 0.61

MDER 0.55

## Optical

medium

beam angle 21°

PstLM ≤ 1.0<sup>2</sup>

SVM ≤ 0.4<sup>2</sup>

## Electrical

DALI-2 single control

48 V

fixture 11.5 W

optical inset 8.6 W

PC3

1 DALI Addr.

## Physical

diameter 45 mm


height 68 mm

0.2 kg

<sup>1</sup> incl. consideration of optical losses

<sup>2</sup> Value of containing product at full load (undimmed)


## Light distribution



medium 21°

h (m)	E0° (lx)	ø (m)
1	2000	0.38
2	500	0.76
3	220	1.14
4	120	1.52
5	80	1.90

## Product drawing



## Installation instructions



[050-0131E3XM] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.  
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

01.05.2025