

w201 Extra small pendant s1 suspended

MOVE IT 25 with hook

050-0461418



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

black , RAL 9005 ¹

IP20

494 lm

LED

2700 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

Optical

flood

beam angle 91°

Electrical

non DIM

7.9 W

PC3 350mA

63 lm/W

Physical

diameter 52 mm


height 130 mm

0.7 kg

¹ RAL code

Decorative pendant light inset made of aluminium; cone-shaped shade; surface black powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 3500mm suspension, incl. feed (black), can be individually shortened, incl. ceiling mounting ring + hook (black) for multiple positioning of the luminaire in the room; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3 350mA; non-dimmable; light source not replaceable; control gear replaceable by an authorized professional;


Light distribution



flood 91°

h (m)	EO° (lx)	ø (m)
1	241	2.05
2	60	4.09
3	27	6.14
4	15	8.19
5	10	10.24

Product drawing



Installation instructions



Lighting calculator

