

# w201 Extra small pendant s3 suspended

MOVE IT 25  
050-0453438



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



**General**

Ceiling , Suspended \_\_\_\_\_

black , RAL 9005 <sup>1</sup> \_\_\_\_\_

IP20 \_\_\_\_\_

519 lm \_\_\_\_\_

**LED**

2700 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L90 / 50000 h \_\_\_\_\_

initial MacAdam ≤ 3 SDCM \_\_\_\_\_

**Optical**

flood \_\_\_\_\_

beam angle 90° \_\_\_\_\_

**Electrical**

DALI-2 \_\_\_\_\_

7.9 W \_\_\_\_\_

PC3 350mA \_\_\_\_\_

66 lm/W \_\_\_\_\_

**Physical**

diameter 151 mm \_\_\_\_\_


height 51 mm \_\_\_\_\_

0.73 kg \_\_\_\_\_

<sup>1</sup> RAL code

Decorative pendant light inset made of aluminium; cone-shaped shade; surface black powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 3000mm suspension, incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3 350mA; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable; control gear replaceable by an authorized professional;


## Light distribution



flood 90°

h (m)	EO° (lx)	ø (m)
1	240	2.01
2	60	4.02
3	27	6.04
4	15	8.05
5	10	10.06

## Product drawing



## Installation instructions



## Lighting calculator



[‘050-0453438’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.  
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com