

w201Extra small pendant s3 suspended

MOVE IT 25 / 25 S / 45
050-0453437



Project / Type _____

Notes _____

Count / Date _____



Decorative pendant light inset made of aluminium; cone-shaped shade; surface white powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 3000mm suspension, incl. feed (white), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3; 48 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable; control gear replaceable by an authorized professional;



General

Ceiling , Suspended
white , RAL 9016 ¹
IP20
572 lm
optical inset 96 lm/W²

LED

2700 K
CRI ≥ 90
L90 / 50000 h
initial MacAdam ≤ 3 SDCM

Optical

flood
beam angle 91°
PstLM ≤ 1.0 ³
SVM ≤ 0.4 ³


Electrical

DALI-2
48 V
fixture 7.9 W
optical inset 5.9 W
PC3

Physical

diameter 151 mm
height 51 mm
0.5 kg


Light distribution



flood 91°

| h (m) | EO° (lx) | ø (m) |
|-------|----------|-------|
| 1 | 264 | 2.02 |
| 2 | 66 | 4.05 |
| 3 | 29 | 6.07 |
| 4 | 17 | 8.10 |
| 5 | 11 | 10.12 |

Product drawing



¹ RAL code ² incl. consideration of optical losses
³ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

