

# ARY cable suspended

MOVE IT 25

050-0511D38M



Project / Type

Notes

Count / Date



Decorative pendant light inset made of aluminium; surface black powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 1500mm suspension, incl. feed (black), can be individually shortened; shades available as accessory in RAL colours velvet beige, madeira brown, kingfisher grey, woodpecker olive, signal white or signal black; accessories are listed separately; passive cooling of the LEDs through improved heat sink geometry; with CSP (Chip-Scale-Packaging) technology for maximum efficiency; no multiple shadows; light colour: tunable white diodes (2200-4000 K); binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; min. 95% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 21° beam; degree of protection IP20; PC3 48V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable;



### General

Ceiling , Track Suspended

black , RAL9005 <sup>1</sup>

IP20

269 lm

### LED

tunable white

2200 K - 4000 K

CRI  $\geq 90$

L95 / 50000 h

initial MacAdam  $\leq 3$  SDCM

MR 0.4

MDER 0.37

### Optical

medium

beam angle 21°

### Electrical

DALI-2

5.4 W

PC3 48V

50 lm/W

1 DALI Addr.

### Physical


cable 1500 mm

diameter 47 mm

height 110 mm

0.35 kg


### Light distribution



medium 21°

h (m)	EO° (lx)	ø (m)
1	1370	0.38
2	340	0.76
3	150	1.14
4	90	1.52
5	50	1.90

### Product drawing



<sup>1</sup> RAL code

### Installation instructions



### Lighting calculator

