

w201 Extra small pendant s2 suspended

MOVE IT 25 / 25 S / 45
050-0452418



Project / Type

Notes

Count / Date



General

Ceiling | Suspended

black | RAL 9005 ¹

IP20

520 lm

optical inset 88 lm/W ²

LED

2700 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

Optical

flood | beam angle 91°

PstLM ≤ 1.0 ³ | SVM ≤ 0.4 ³

Electrical

non DIM

PC3 | 48 V

fixture 7.9 W

optical inset 5.9 W

Physical


diameter 91 mm | height 94 mm

0.5 kg

Decorative pendant light inset made of aluminium; cone-shaped shade; surface black powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 3000mm suspension, incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3; 48 V; non-dimmable; light source not replaceable; control gear replaceable by an authorized professional;

¹ RAL code ² incl. consideration of optical losses
³ Value of containing product at full load (undimmed)


Light distribution



flood 91°

h (m)	EO° (lx)	ø (m)
1	246	2.02
2	61	4.04
3	27	6.07
4	15	8.09
5	10	10.11

Product drawing



Installation instructions



Lighting calculator

