

w201Extra small pendant s2 suspended

MOVE IT 25
050-0452418



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Suspended _____

black , RAL 9005 ¹ _____

IP20 _____

520 lm _____

LED

2700 K _____

CRI ≥ 90 _____

L90 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

Optical

flood _____

beam angle 91° _____

Electrical

non DIM _____

7.9 W _____

PC3 350mA _____

66 lm/W _____

Physical

diameter 91 mm _____


height 94 mm _____

0.7 kg _____

Decorative pendant light inset made of aluminium; cone-shaped shade; surface black powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 3000mm suspension, incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3 350mA; non-dimmable; light source not replaceable; control gear replaceable by an authorized professional;


¹ RAL code

Light distribution



flood 91°		
h (m)	EO° (lx)	ø (m)
1	246	2.02
2	61	4.04
3	27	6.07
4	15	8.09
5	10	10.11

Product drawing



Installation instructions



Lighting calculator

