

w201 Extra small pendant s2 suspended

MOVE IT 25 / 25 S / 45
050-0452417



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling | Suspended _____

traffic white | RAL 9016 _____

IP20 _____

572 lm _____

optical inset 96 lm/W ¹ _____

LED

2700 K _____

CRI ≥ 90 _____

L90 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

Optical

flood | beam angle 91° _____

PstLM ≤ 1.0 ² | SVM ≤ 0.4 ² _____

Electrical

non DIM _____

PC3 | 48 V _____

fixture 7.9 W _____

optical inset 5.9 W _____

Physical


diameter 91 mm | height 94 mm _____

0.5 kg _____

Decorative pendant light inset made of aluminium; cone-shaped shade; surface traffic white powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 3000mm suspension, incl. feed (traffic white), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3; 48 V; non-dimmable; light source not replaceable; control gear replaceable by an authorized professional;

¹ incl. consideration of optical losses
² Value of containing product at full load (undimmed)


Light distribution



flood 91°

h (m)	EO [®] (lx)	ø (m)
1	264	2.02
2	66	4.05
3	29	6.07
4	17	8.10
5	11	10.12

Product drawing



Installation instructions



Lighting calculator

