

JUST 45 MOVE IT 25 / 25 S / 45

050-0131D38F



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling / Wall , Track
 tilt max 90°
 rotation 360°
 black , RAL 9005 ¹
 IP20
 674 lm
 optical inset 79 lm/W²

LED

tunable white
 2700 K - 6500 K
 CRI ≥ 90
 L90 / 50000 h
 initial MacAdam ≤ 3 SDCM
 R_g: 97 , R_f: 88 , R_{f(1-15)}: 88
 MR 1.15
 MDER 1.04

Optical

flood
 beam angle 42°
 P_{stLM} ≤ 1.0 ³
 SVM ≤ 0.4 ³

Electrical

DALI-2 DT8 single control
 48 V
 fixture 11.3 W
 optical inset 8.5 W
 PC3
 1 DALI Addr.


Physical

diameter 45 mm
 height 68 mm
 0.2 kg

¹ RAL code ² incl. consideration of optical losses
³ Value of containing product at full load (undimmed)

Cylindrical spotlight in aluminium; surface black powder coated; 360° rotatable and 90° tiltable; spotlight can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour: tunable white diodes (2700-6500 K); binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 42° beam; degree of protection IP20; PC3; 48 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); optical attachment available as accessory; accessories are listed separately; light source not replaceable;


Light distribution



flood 42°

h (m)	E0° (lx)	ø (m)
1	1350	0.77
2	340	1.55
3	150	2.32
4	80	3.10
5	50	3.87

Product drawing



Installation instructions

