

JUST 45 MOVE IT 25 / 25 S / 45

050-0131D38F



Project / Type _____
Notes _____
Count / Date _____



General

Ceiling / Wall | Track
tilt max 90°
rotation 360°
black | RAL 9005 ¹
IP20
674 lm
optical inset 79 lm/W ²

LED

tunable white | 2700 K - 6500 K
CRI ≥ 90
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
R_g: 97 | R_r: 88 | R_{t(1-5)}: 88
MR 1.15 | MDER 1.04

Optical

flood | beam angle 42°
PstLM ≤ 1.0 ³ | SVM ≤ 0.4 ³


Electrical

DALI-2 DT8 | 1 DALI Addr.
PC3 | 48 V
fixture 11.3 W
optical inset 8.5 W

Physical

diameter 45 mm | height 68 mm
0.2 kg


Light distribution



flood 42°

h (m)	E0° (lx)	ø (m)
1	1350	0.77
2	340	1.55
3	150	2.32
4	80	3.10
5	50	3.87

Product drawing



¹ RAL code ² incl. consideration of optical losses
³ Value of containing product at full load (undimmed)

Installation instructions



JUST 45 MOVE IT 25 / 25

S / 45

050-0131D38F



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.96	0.94	0.92	0.9
LSF	1	1	1	1	1

MF

MF

LMF^a

LMF × RSMF × LLMF × LSF

Maintenance Factor

Luminaire Maintenance Factor

RSMF^a

LLMF

LSF

Room Surface Maintenance Factor

Lamp Lumens Maintenance Factor

Lamp Survival Factor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Optical accessories

HONEYCOMB LOUVER

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
jet black	42	007-1965188



Optical accessories

OVAL LENS

Ø (MM)	ARTICLE NUMBER(S)
42	007-1965880



SOFT LENS

Ø (MM)	ARTICLE NUMBER(S)
42	007-1965980



WALLWASHER LENS

Ø (MM)	ARTICLE NUMBER(S)
42	007-1965780

