

w201 Extra small pendant s1 suspended

MOVE IT 25 / 25 S / 45
050-0451417



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling | Suspended _____

white | RAL 9016 ¹ _____

IP20 _____

544 lm _____

optical inset 92 lm/W ² _____

LED

2700 K _____

CRI ≥ 90 _____

L90 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

Optical

flood | beam angle 91° _____

PstLM ≤ 1.0 ³ | SVM ≤ 0.4 ³ _____

Electrical

non DIM _____

PC3 | 48 V _____

fixture 7.9 W _____

optical inset 5.9 W _____

Physical


diameter 52 mm | height 130 mm _____

0.4 kg _____

Decorative pendant light inset made of aluminium; cone-shaped shade; surface white powder coated; light inset can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 3000mm suspension, incl. feed (white), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3; 48 V; non-dimmable; light source not replaceable; control gear replaceable by an authorized professional;


¹ RAL code ² incl. consideration of optical losses
³ Value of containing product at full load (undimmed)

Light distribution



flood 91°		
h (m)	EO° (lx)	ø (m)
1	251	2.02
2	63	4.05
3	28	6.07
4	16	8.10
5	10	10.12

Product drawing



Installation instructions



Lighting calculator

