

# PIVOT MOVE IT 25 / 25 S

## suspended

050-0324L380



Project / Type


Notes

Count / Date




Cylindrical, decorative-graphic light inset made of aluminium and satinised PMMA for homogeneous illumination; surface anodised black; light inset can be installed and moved without tools by means of magnetic holders+locking; pendant fitting with 1500mm cable suspension; suitable for two MOVE IT 25 / 25 S profiles as well as one MOVE IT 25 / 25 S profile (axial arrangement); holders 360° rotatable; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; with CSP (Chip-Scale-Packaging) technology for maximum efficiency; light colour: tunable white diodes (1800-4000 K); binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3 48V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

### Light distribution



### Product drawing



### General

Ceiling , Track

rotation 360°

black , RAL9005 <sup>1</sup>

1300 lm

Beam Angle Correspondence Sphere (360°)

Non-directional light source

IP20

1300 lm

Chromaticity Coordinate X: 0.388

Chromaticity Coordinate Y: 0.382

### LED

tunable white

1800 K - 4000 K

CRI ≥ 80

L90 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

MR 0.72

MDER 0.66

### Electrical

DALI-2

10.6 W

PC3 48V

123 lm/W

1 DALI Addr.

### Physical

length 1210 mm

width 33 mm

height 33 mm

0.5 kg

<sup>1</sup> RAL code

### Installation instructions



### Lighting calculator

