

PIVOT MOVE IT 25 / 25 S

suspended


050-03244180



Project / Type

Notes

Count / Date



General

Ceiling , Track Suspended

rotation 360°

black , RAL9005 ¹

1980 lm/m

IP20

2380 lm

LED

2700 K

CRI ≥ 80

L90 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

MR 0.47

MDER 0.42

Electrical

non DIM

21.2 W

PC3 48V

112 lm/W

18 W/m

Physical

length 1210 mm

width 33 mm


height 33 mm

0.5 kg


¹ RAL code

Cylindrical, decorative-graphic light inset made of aluminium and satinised PMMA for homogeneous illumination; surface anodised black; light inset can be installed and moved without tools by means of magnetic holders+locking; pendant fitting with 1500mm cable suspension; suitable for two MOVE IT 25 / 25 S profiles as well as one MOVE IT 25 / 25 S profile (axial arrangement); holders 360° rotatable; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; with CSP (Chip-Scale-Packaging) technology for maximum efficiency; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3 48V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; non-dimmable; light source replaceable by an authorized professional;

Light distribution



Product drawing



Installation instructions



Lighting calculator

