

JUST 32 FOCUS

MOVE IT 25


050-0111437



Project / Type

Notes

Count / Date



General

Ceiling / Wall , Track

tilt max 90°

rotation 360°

white , RAL9016 ¹

IP20

296²-367³ lm

LED

2700 K

CRI ≥ 90

L95 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 99 , R_f: 91 , R₍₁₋₁₅₎: 89

MR 0.54

MDER 0.49

Optical

variable focus

beam angle 17°²-43°³

Electrical

DALI-2 single control

8.3 W

PC3 48V

36²-44³ lm/W

1 DALI Addr.

Physical


diameter 32 mm

height 73 mm

0.2 kg


Cylindrical spotlight in aluminium; surface white powder coated; 360° rotatable and 90° tiltable; spotlight can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 95% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality plano-convex glass lens; precise object focusing through adjustable lens; adjustable beam angle of 17° - 43°; focusing by means of patented slider on the spotlight head; degree of protection IP20; PC3 48V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); optical attachment available as accessory; accessories are listed separately; light source not replaceable;

Light distribution



variable focus 43°


h (m)	E0° (lx)	ø (m)
1	661	0.80
2	165	1.59
3	73	2.39
4	41	3.18
5	26	3.98



variable focus 17°

h (m)	E0° (lx)	ø (m)
1	2290	0.30
2	570	0.59
3	250	0.89
4	140	1.19
5	90	1.49

Product drawing



¹ RAL code ² beam angle min ³ beam angle max

Installation instructions

