

# PIVOT MOVE IT 25 / 25 S / 45 suspended

050-03235380



Project / Type


Notes

Count / Date




Cylindrical, decorative-graphic light inset made of aluminium and satinised PMMA for homogeneous illumination; surface anodised black; light inset can be installed and moved without tools by means of magnetic holders+locking; pendant fitting with 1500mm cable suspension; suitable for two MOVE IT 25 / 25 S / 45 profiles as well as one MOVE IT 25 / 25 S / 45 profile (axial arrangement); holders 360° rotatable; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; with CSP (Chip-Scale-Packaging) technology for maximum efficiency; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3; 48 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

## Light distribution



## Product drawing



### General

Ceiling | Track Suspended  
rotation 360°  
black | RAL 9005 <sup>1</sup>  
IP20  
1890 lm  
2100 lm/m  
optical inset 170 lm/W <sup>2</sup>

### LED

3000 K  
CRI ≥ 80  
L90 / 50000 h  
initial MacAdam ≤ 3 SDCM  
MR 0.54 | MDER 0.49

### Optical

opal (lambertsch)  
PstLM ≤ 1.0 <sup>3</sup> | SVM ≤ 0.4 <sup>3</sup>

### Electrical

DALI-2 | 1 DALI Addr.  
PC3 | 48 V  
fixture 15.9 W  
optical inset 11.1 W  
18 W/m

### Physical

length 910 mm | width 33 mm | height 33 mm  
0.4 kg

<sup>1</sup> RAL code <sup>2</sup> incl. consideration of optical losses  
<sup>3</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Lighting calculator

