

MOUNTING HOUSING

600 trim linear

049-8856037



| | |
|----------------|--|
| Project / Type | |
| Notes | |
| Count / Date | |



Installation housing in pressed steel sheet with rectangular cut-out; with wrap around edge; suitable for ceiling thickness of 12.5 mm; 6 non-reversible plug and play connector sockets for power supply to the spotlights; spotlight can be installed and moved without tools by means of magnetic holders; hot plug protection; surface traffic white powder coated; degree of protection IP20; PC1; incl. DALI-2 converter; all spotlights together DALI dimmable; control gear replaceable by an authorized professional;

Product drawing



General

| |
|---------------------------------------|
| Ceiling Recessed |
| traffic white RAL 9016 ¹ |
| IP20 |

Electrical

| |
|---|
| DALI-2 2 DALI Addr. |
| PC1 220-240 V |
| PC2 |
| 25 W |
| Dim DALI, Push Dim, Dim DSI, Dim Dali 2 |
| min 198 V |
| max 264 V |
| Constant Current |
| min 50 Hz |
| max 60 Hz |

Physical

| |
|--|
| length 644 mm width 271 mm height 120 mm |
|--|

Cutout

| |
|---|
| length 635 mm width 135 mm |
| min. ceiling thickness 12.5 mm max. ceiling thickness 12.5 mm |
| recessed depth 175 mm |

¹ RAL code

Installation instructions

