

MOUNTING HOUSING

600 trim linear

049-8856037



Project / Type	
Notes	
Count / Date	



Installation housing in pressed steel sheet with rectangular cut-out; with wrap around edge; suitable for ceiling thickness of 12.5 mm; 6 non-reversible plug and play connector sockets for power supply to the spotlights; spotlight can be installed and moved without tools by means of magnetic holders; hot plug protection; surface traffic white powder coated; degree of protection IP20; PC1; incl. DALI-2 converter; all spotlights together DALI dimmable; control gear replaceable by an authorized professional;

Product drawing



General

Ceiling , Recessed
traffic white , RAL 9016 ¹
IP20

Electrical

DALI-2
220-240 V
PC1
2 DALI Addr.
PC2
25 W
Dim DALI, Push Dim, Dim DSI, Dim Dali 2
min 198 V
max 264 V
Constant Current
min 50 Hz
max 60 Hz

Physical

length 644 mm
width 271 mm
height 120 mm

Cutout

length 635 mm
width 135 mm
min. ceiling thickness 12.5 mm
max. ceiling thickness 12.5 mm
recessed depth 175 mm

¹ RAL code

Installation instructions





Project / Type

Notes

Count / Date

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Converters
B10	19
B13	24
B16	31
B20	40
C10	31
C13	40
C16	51
C20	66