


PIVOT MOVE IT 25 / 25 S

suspended

050-03224180



Project / Type _____
 Notes _____
 Count / Date _____



General

Ceiling , Track Suspended _____
 rotation 360° _____
 black , RAL9005 ¹ _____
 1980 lm/m _____
 IP20 _____
 1190 lm _____

LED

2700 K _____
 CRI ≥ 80 _____
 L90 / 50000 h _____
 photobio. safety RG 0 - no Risk _____
 initial MacAdam ≤ 3 SDCM _____
 MR 0.47 _____
 MDER 0.42 _____

Electrical

non DIM _____
 10.6 W _____
 PC3 48V _____
 112 lm/W _____
 18 W/m _____


Physical

length 610 mm _____
 width 33 mm _____
 height 33 mm _____
 0.35 kg _____


Cylindrical, decorative-graphic light inset made of aluminium and satinised PMMA for homogeneous illumination; surface anodised black; light inset can be installed and moved without tools by means of magnetic holders+locking; pendant fitting with 1500mm cable suspension; suitable for two MOVE IT 25 / 25 S profiles as well as one MOVE IT 25 / 25 S profile (axial arrangement); holders 360° rotatable; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; with CSP (Chip-Scale-Packaging) technology for maximum efficiency; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3 48V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; non-dimmable; light source replaceable by an authorized professional;

¹ RAL code

Light distribution



Product drawing



Installation instructions



Lighting calculator

