

# MOUNTING HOUSING

## 300 trim linear

049-8853038



Project / Type	
Notes	
Count / Date	



Installation housing in pressed steel sheet with rectangular cut-out; with wrap around edge; suitable for ceiling thickness of 12.5 mm; 3 non-reversible plug and play connector sockets for power supply to the spotlights; spotlight can be installed and moved without tools by means of magnetic holders; hot plug protection; surface jet black powder coated; degree of protection IP20; PC1; incl. DALI-2 converter; all spotlights together DALI dimmable; control gear replaceable by an authorized professional;

### Product drawing



### General

Ceiling , Recessed	
jet black , RAL 9005 <sup>1</sup>	
IP20	

### Electrical

DALI-2	
220-240 V	
PC1	
1 DALI Addr.	
PC2	
25 W	
Dim DALI, Push Dim, Dim DSI, Dim Dali 2	
min 198 V	
max 264 V	
Constant Current	
min 50 Hz	
max 60 Hz	

### Physical

length 344 mm	
width 254 mm	
height 120 mm	

### Cutout

length 335 mm	
width 135 mm	
min. ceiling thickness 12.5 mm	
max. ceiling thickness 12.5 mm	
recessed depth 175 mm	

<sup>1</sup> RAL code

### Installation instructions





Project / Type

Notes

Count / Date

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Converters
B10	19
B13	24
B16	31
B20	40
C10	31
C13	40
C16	51
C20	66