

# MOUNTING HOUSING 300

## trim linear


049-8853038



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



### General

Ceiling , Recessed \_\_\_\_\_

jet black , RAL 9005 <sup>1</sup> \_\_\_\_\_

IP20 \_\_\_\_\_

### Electrical

DALI-2 \_\_\_\_\_

PC1 220-240V \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_

### Physical

length 344 mm \_\_\_\_\_

width 254 mm \_\_\_\_\_

height 120 mm \_\_\_\_\_

2.6 kg \_\_\_\_\_

### Cutout

length 335 mm \_\_\_\_\_

width 135 mm \_\_\_\_\_

min. ceiling thickness 12.5 mm \_\_\_\_\_


max. ceiling thickness 12.5 mm \_\_\_\_\_

recessed depth 175 mm \_\_\_\_\_

Installation housing in pressed steel sheet with rectangular cut-out; with wrap around edge; suitable for ceiling thickness of 12.5 mm; 3 non-reversible plug and play connector sockets for power supply to the spotlights; spotlight can be installed and moved without tools by means of magnetic holders; hot plug protection; surface jet black powder coated; degree of protection IP20; PC1 220-240V; incl. DALI-2 converter; all spotlights together DALI dimmable; control gear replaceable by an authorized professional;

<sup>1</sup> RAL code

## Product drawing



## Installation instructions

