

# MOUNTING HOUSING

## 300 trim linear

049-8853037



Project / Type	
Notes	
Count / Date	



Installation housing in pressed steel sheet with rectangular cut-out; with wrap around edge; suitable for ceiling thickness of 12.5 mm; 3 non-reversible plug and play connector sockets for power supply to the spotlights; spotlight can be installed and moved without tools by means of magnetic holders; hot plug protection; surface traffic white powder coated; degree of protection IP20; PC1; incl. DALI-2 converter; all spotlights together DALI dimmable; control gear replaceable by an authorized professional;

### Product drawing



### General

Ceiling , Recessed
traffic white , RAL 9016 <sup>1</sup>
IP20

### Electrical

DALI-2
220-240 V
PC1
1 DALI Addr.
PC2
25 W
Dim DALI, Push Dim, Dim DSI, Dim Dali 2
min 198 V
max 264 V
Constant Current
min 50 Hz
max 60 Hz

### Physical

length 344 mm
width 254 mm
height 120 mm

### Cutout

length 335 mm
width 135 mm
min. ceiling thickness 12.5 mm
max. ceiling thickness 12.5 mm
recessed depth 175 mm

<sup>1</sup> RAL code

### Installation instructions





Project / Type

Notes

Count / Date

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Converters
B10	19
B13	24
B16	31
B20	40
C10	31
C13	40
C16	51
C20	66