

# MOUNTING HOUSING

## 600 trimless linear

049-8846037




Project / Type	
Notes	
Count / Date	



Installation housing in pressed steel sheet with rectangular cut-out; for trimless installation in plasterboard ceilings; special edge design with perforations for better adhesion of filler; suitable for ceiling thickness of 12.5 mm; 6 non-reversible plug and play connector sockets for power supply to the spotlights; spotlight can be installed and moved without tools by means of magnetic holders; hot plug protection; surface traffic white powder coated; degree of protection IP20; PC1; incl. DALI-2 converter; all spotlights together DALI dimmable; control gear replaceable by an authorized professional;

### Product drawing



### General

Ceiling   Recessed
traffic white   RAL 9016 <sup>1</sup>
IP20

### Electrical

DALI-2   2 DALI Addr.
PC1   220-240 V
PC2
25 W
Dim DALI, Push Dim, Dim DSI, Dim Dali 2
min 198 V
max 264 V
Constant Current
min 50 Hz
max 60 Hz

### Physical

length 608 mm   width 269 mm   height 120 mm
--

### Cutout

length 608 mm   width 136 mm
min. ceiling thickness 12.5 mm   max. ceiling thickness 12.5 mm
recessed depth 175 mm

<sup>1</sup> RAL code

### Installation instructions

