

MOUNTING HOUSING

600 trimless linear

049-8846037




Project / Type	
Notes	
Count / Date	



Installation housing in pressed steel sheet with rectangular cut-out; for trimless installation in plasterboard ceilings; special edge design with perforations for better adhesion of filler; suitable for ceiling thickness of 12.5 mm; 6 non-reversible plug and play connector sockets for power supply to the spotlights; spotlight can be installed and moved without tools by means of magnetic holders; hot plug protection; surface traffic white powder coated; degree of protection IP20; PC1; incl. DALI-2 converter; all spotlights together DALI dimmable; control gear replaceable by an authorized professional;

Product drawing



General

Ceiling Recessed
traffic white RAL 9016 ¹
IP20

Electrical

DALI-2 2 DALI Addr.
PC1 220-240 V
PC2
25 W
Dim DALI, Push Dim, Dim DSI, Dim Dali 2
min 198 V
max 264 V
Constant Current
min 50 Hz
max 60 Hz

Physical

length 608 mm width 269 mm height 120 mm
--

Cutout

length 608 mm width 136 mm
min. ceiling thickness 12.5 mm max. ceiling thickness 12.5 mm
recessed depth 175 mm

¹ RAL code

Installation instructions



MOUNTING HOUSING

600 trimless linear

049-8846037



Project / Type

Notes

Count / Date

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Converters
B10	19
B13	24
B16	31
B20	40
C10	31
C13	40
C16	51
C20	66

