




Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



<b>General</b>	
Ceiling / Wall , Track	_____
rotation 360°	_____
black , RAL 9005 <sup>1</sup>	_____
IP20	_____
2970 lm	_____
1980 lm/m	_____
optical inset 160 lm/W <sup>2</sup>	_____

<b>LED</b>	
2700 K	_____
CRI ≥ 80	_____
L90 / 50000 h	_____
initial MacAdam ≤ 3 SDCM	_____
MR 0.47	_____
MDER 0.42	_____


<b>Optical</b>	
opal (lambertsch)	_____
PstLM ≤ 1.0 <sup>3</sup>	_____
SVM ≤ 0.4 <sup>3</sup>	_____

<b>Electrical</b>	
non DIM	_____
48 V	_____
fixture 26.4 W	_____
optical inset 18.5 W	_____
PC3	_____
18 W/m	_____


<b>Physical</b>	
length 1510 mm	_____
width 33 mm	_____
height 33 mm	_____
0.55 kg	_____

<sup>1</sup> RAL code <sup>2</sup> incl. consideration of optical losses  
<sup>3</sup> Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions

