

# MOUNTING HOUSING

## 300 trimless linear

049-8843037



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



### General

Ceiling , Recessed \_\_\_\_\_  
traffic white , RAL 9016 <sup>1</sup> \_\_\_\_\_  
IP20 \_\_\_\_\_

### Electrical

DALI-2 \_\_\_\_\_  
220-240 V \_\_\_\_\_  
PC1 \_\_\_\_\_  
1 DALI Addr. \_\_\_\_\_  
PC2 \_\_\_\_\_  
25 W \_\_\_\_\_  
Dim DALI, Push Dim, Dim DSI, Dim Dali 2 \_\_\_\_\_  
min 198 V \_\_\_\_\_  
max 264 V \_\_\_\_\_  
Constant Current \_\_\_\_\_  
min 50 Hz \_\_\_\_\_  
max 60 Hz \_\_\_\_\_

### Physical


length 308 mm \_\_\_\_\_  
width 252 mm \_\_\_\_\_  
height 120 mm \_\_\_\_\_

### Cutout

length 308 mm \_\_\_\_\_  
width 136 mm \_\_\_\_\_  
min. ceiling thickness 12.5 mm \_\_\_\_\_  
max. ceiling thickness 12.5 mm \_\_\_\_\_  
recessed depth 175 mm \_\_\_\_\_

Installation housing in pressed steel sheet with rectangular cut-out; for trimless installation in plasterboard ceilings; special edge design with perforations for better adhesion of filler; suitable for ceiling thickness of 12.5 mm; 3 non-reversible plug and play connector sockets for power supply to the spotlights; spotlight can be installed and moved without tools by means of magnetic holders; hot plug protection; surface traffic white powder coated; degree of protection IP20; PC1; incl. DALI-2 converter; all spotlights together DALI dimmable; control gear replaceable by an authorized professional;

### Product drawing



<sup>1</sup> RAL code

### Installation instructions



# MOUNTING HOUSING

## 300 trimless linear

049-8843037



Project / Type

Notes

Count / Date

### Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Converters
B10	19
B13	24
B16	31
B20	40
C10	31
C13	40
C16	51
C20	66