



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



<b>General</b>	
Ceiling / Wall , Track	_____
rotation 360°	_____
black , RAL9005 <sup>1</sup>	_____
2100 lm/m	_____
IP20	_____
2530 lm	_____

<b>LED</b>	
3000 K	_____
CRI ≥ 80	_____
L90 / 50000 h	_____
photobio. safety RG 0 - no Risk	_____
initial MacAdam ≤ 3 SDCM	_____
MR 0.54	_____
MDER 0.49	_____


<b>Electrical</b>	
non DIM	_____
21.2 W	_____
PC3 48V	_____
119 lm/W	_____
18 W/m	_____

<b>Physical</b>	
length 1210 mm	_____
width 33 mm	_____
height 33 mm	_____
0.45 kg	_____


Cylindrical, decorative-graphic light inset made of aluminium and satinised PMMA for homogeneous illumination; surface anodised black; light inset can be installed and moved without tools by means of magnetic holders+locking; suitable for two MOVE IT 25 profiles as well as one MOVE IT 25 profile (axial arrangement); holders 360° rotatable; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; with CSP (Chip-Scale-Packaging) technology for maximum efficiency; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3 48V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; non-dimmable; light source replaceable by an authorized professional;

<sup>1</sup> RAL code

Light distribution



Product drawing



Installation instructions

