

MOUNTING HOUSING with glowing round


049-8823537



Project / Type


Notes

Count / Date



Recessed housing made of pressed steel sheet for flush installation in plasterboard ceilings, underside of aluminium-reinforced plaster (paintable); with round cut-out; no break-out of edges; for trimless installation in plasterboard ceilings; suitable for ceiling thickness of 8-25 mm; 3 non-reversible plug and play connector sockets for power supply to the spotlights; spotlight can be installed and moved without tools by means of magnetic holders; hot plug protection; indirect light component in housing; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; indirect component in the channel continuously adjustable dimming via DALI; surface traffic white powder coated; degree of protection IP20; PC1 220-240V; incl. DALI-2 converter; all spotlights together DALI dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Product drawing



General

Ceiling , Recessed

traffic white , RAL 9016 ¹

Beam Angle Correspondence Sphere (360°)

Non-directional light source

IP20

Chromaticity Coordinate X: 0.445

Chromaticity Coordinate Y: 0.407

LED

3000 K

CRI ≥ 90

initial MacAdam ≤ 3 SDCM

R_g: 101 , R_f: 91 , R_{t(1-15)}: 89

MR 0.56

MDER 0.51

Electrical

DALI-2

PC1 220-240V

1 DALI Addr.

Physical

length 260 mm

width 260 mm

height 120 mm

5.2 kg

Cutout

length 270 mm

width 270 mm

min. ceiling thickness 8 mm

max. ceiling thickness 25 mm

recessed depth 140 mm

¹ RAL code

Installation instructions

