

MOUNTING HOUSING round

049-8803038



Project / Type

Notes

Count / Date



Recessed housing made of pressed steel sheet for flush installation in plasterboard ceilings, underside of aluminium-reinforced plaster (paintable); with round cut-out; no break-out of edges; for trimless installation in plasterboard ceilings; suitable for ceiling thickness of 8-25 mm; 3 non-reversible plug and play connector sockets for power supply to the spotlights; spotlight can be installed and moved without tools by means of magnetic holders; hot plug protection; surface jet black powder coated; degree of protection IP20; PC1; incl. DALI-2 converter; all spotlights together DALI dimmable; control gear replaceable by an authorized professional;

Product drawing



General

Ceiling | Recessed

jet black | RAL 9005 ¹

IP20

Electrical

DALI-2 | 1 DALI Addr.

PC1 | 220-240 V

PC2

25 W

Dim DALI, Push Dim, Dim DSI, Dim Dali 2

min 198 V

max 264 V

Constant Current

min 50 Hz

max 60 Hz

Physical

length 260 mm | width 260 mm | height 120 mm

Cutout

length 270 mm | width 270 mm

min. ceiling thickness 8 mm | max. ceiling thickness 25 mm

recessed depth 140 mm

¹ RAL code

Installation instructions



MOUNTING HOUSING

round

049-8803038



Project / Type

Notes

Count / Date

Circuit Breaker Types

| Automatic Circuit Breaker Type | Number of Converters |
|--------------------------------|----------------------|
| B10 | 19 |
| B13 | 24 |
| B16 | 31 |
| B20 | 40 |
| C10 | 31 |
| C13 | 40 |
| C16 | 51 |
| C20 | 66 |

