

# MOUNTING HOUSING round

049-8803037



|                |  |
|----------------|--|
| Project / Type |  |
| Notes          |  |
| Count / Date   |  |



Recessed housing made of pressed steel sheet for flush installation in plasterboard ceilings, underside of aluminium-reinforced plaster (paintable); with round cut-out; no break-out of edges; for trimless installation in plasterboard ceilings; suitable for ceiling thickness of 8-25 mm; 3 non-reversible plug and play connector sockets for power supply to the spotlights; spotlight can be installed and moved without tools by means of magnetic holders; hot plug protection; surface traffic white powder coated; degree of protection IP20; PC1; incl. DALI-2 converter; all spotlights together DALI dimmable; control gear replaceable by an authorized professional;

## Product drawing



## General

|                                       |
|---------------------------------------|
| Ceiling   Recessed                    |
| traffic white   RAL 9016 <sup>1</sup> |
| IP20                                  |

## Electrical

|   |
|---|
| DALI-2   1 DALI Addr.                   |
| PC1   220-240 V                         |
| PC2                                     |
| 25 W                                    |
| Dim DALI, Push Dim, Dim DSI, Dim Dali 2 |
| min 198 V                               |
| max 264 V                               |
| Constant Current                        |
| min 50 Hz                               |
| max 60 Hz                               |

## Physical

|  |
|--|
| length 260 mm   width 260 mm   height 120 mm |
|--|

## Cutout

|  |
|--|
| length 270 mm   width 270 mm                               |
| min. ceiling thickness 8 mm   max. ceiling thickness 25 mm |
| recessed depth 140 mm                                      |

<sup>1</sup> RAL code

## Installation instructions

