

WALLWASHER

MOVE IT 25

050-0232438A



Project / Type

Notes

Count / Date



General

Ceiling / Wall , Track

black , RAL9005 ¹

IP20

959 lm

LED

2700 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 99 , R_f: 90 , R₍₁₋₁₅₎: 88

MR 0.53

MDER 0.48

Optical

wallwasher

Electrical

DALI-2 single control

15.8 W

PC3 48V

61 lm/W

1 DALI Addr.

Physical

length 450 mm

width 24 mm

height 112 mm

0.64 kg


¹ RAL code

Installation instructions



Linear light inset made of aluminium; surface anodised black; light inset can be installed and moved without tools by means of magnetic holders+locking; protruding from profile system; power supplied via MOVE IT system track profile; hot plug protection; with specially computed, asymmetrical reflector for homogeneous lighting intensity; passive cooling of the LEDs through improved heat sink geometry; with CSP (Chip-Scale-Packaging) technology for maximum efficiency; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC3 48V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable;

Light distribution



Product drawing

