

SPOT LINE

MOVE IT 25

050-0222518M



Project / Type

Notes

Count / Date



Linear light inset made of aluminium; surface anodised black; light inset can be installed and moved without tools by means of magnetic holders+locking; flush with profile system; power supplied via MOVE IT system track profile; hot plug protection; fitted with single LED light points; passive cooling of the LEDs through improved heat sink geometry; with CSP (Chip-Scale-Packaging) technology for maximum efficiency; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; inserted lenses with medium radiation characteristic 31°; UGR ≤ 16 ; degree of protection IP20; PC3; 48 V; non-dimmable; light source not replaceable;



General

Ceiling / Wall | Track

black | RAL 9005 ¹

IP20

1450 lm

optical inset 96 lm/W ²

LED

3000 K

CRI ≥ 97

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 92 | R_r: 86 | R_{t(1-15)}: 94

MR 0.53 | MDER 0.48

Optical

medium

UGR ≤ 16

PstLM ≤ 1.0 ³ | SVM ≤ 0.4 ³

Electrical

non DIM

PC3 | 48 V

fixture 17.9 W


optical inset 15.2 W

Physical

length 605 mm | width 25 mm | height 45 mm

0.57 kg

Light distribution



Product drawing



¹ RAL code ² incl. consideration of optical losses
³ Value of containing product at full load (undimmed)

Installation instructions

