

# SPOT LINE

MOVE IT 25  
050-0220538M



Project / Type


Notes

Count / Date



Linear light inset made of aluminium; surface anodised black; light inset can be installed and moved without tools by means of magnetic holders+locking; flush with profile system; power supplied via MOVE IT system track profile; hot plug protection; fitted with single LED light points; passive cooling of the LEDs through improved heat sink geometry; with CSP (Chip-Scale-Packaging) technology for maximum efficiency; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 97$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; inserted lenses with medium radiation characteristic 31°; UGR  $\leq 16$ ; degree of protection IP20; PC3 48V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source not replaceable;

## Light distribution



## Product drawing



### General

Ceiling / Wall , Track

black , RAL9005 <sup>1</sup>

IP20

363 lm

### LED

3000 K

CRI  $\geq 97$

L80 / 50000 h

initial MacAdam  $\leq 3$  SDCM

R<sub>g</sub>: 92 , R<sub>f</sub>: 86 , R<sub>(1-15)</sub>: 94

MR 0.53

MDER 0.48

### Optical

medium

UGR < 16

### Electrical

DALI-2 single control

4.5 W

PC3 48V

81 lm/W

1 DALI Addr.

### Physical

length 155 mm

width 25 mm

height 45 mm

0.12 kg

<sup>1</sup> RAL code

## Installation instructions

