

SPOT LINE

MOVE IT 25
050-0220438M



Project / Type	
Notes	
Count / Date	



General

Ceiling / Wall , Track	
black , RAL 9005 ¹	
IP20	
336 lm	
optical inset 89 lm/W ²	

LED

2700 K	
CRI ≥ 97	
L95 / 50000 h	
initial MacAdam ≤ 3 SDCM	
R _g : 101 , R _f : 96 , R _{f(1-5)} : 96	
MR 0.59	
MDER 0.53	

Optical

medium	
UGR ≤ 16	
PstLM ≤ 1.0 ³	
SVM ≤ 0.4 ³	

Electrical


DALI-2 single control	
48 V	
fixture 4.5 W	
optical inset 3.8 W	
PC3	
1 DALI Addr.	

Physical

length 155 mm	
width 25 mm	
height 45 mm	
0.17 kg	

¹ RAL code ² incl. consideration of optical losses
³ Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions



SPOT LINE

MOVE IT 25
050-0220438M



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.98	0.97	0.96	0.95
LSF	1	1	1	1	1

MF

MF

LMF^a

LMF × RSMF × LLMF × LSF

Maintenance Factor

Luminaire Maintenance Factor

RSMF^a

LLMF

LSF

Room Surface Maintenance Factor

Lamp Lumens Maintenance Factor

Lamp Survival Factor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

