

SPOT LINE

MOVE IT 25
050-0220418M



Project / Type


Notes

Count / Date



Linear light inset made of aluminium; surface anodised black; light inset can be installed and moved without tools by means of magnetic holders+locking; flush with profile system; power supplied via MOVE IT system track profile; hot plug protection; fitted with single LED light points; passive cooling of the LEDs through improved heat sink geometry; with CSP (Chip-Scale-Packaging) technology for maximum efficiency; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97 ; min. 95% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; inserted lenses with medium radiation characteristic 31°; UGR ≤ 16 ; degree of protection IP20; PC3 48V; non-dimmable; light source not replaceable;

Light distribution



Product drawing



General

Ceiling / Wall , Track

black , RAL9005 ¹

IP20

336 lm

LED

2700 K

CRI ≥ 97

L95 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 101 , R_r: 96 , R_{f(1-5)}: 96

MR 0.59

MDER 0.53

Optical

medium

UGR < 16

Electrical

non DIM

4.4 W

PC3 48V

76 lm/W

Physical

length 155 mm

width 25 mm

height 45 mm

0.11 kg

¹ RAL code

Installation instructions

