

OPAL HIGH PERFORMANCE

MOVE IT 25

050-0218438H



| | |
|----------------|--|
| Project / Type | |
| Notes | |
| Count / Date | |



General

| | |
|-------------------------------------|--|
| Ceiling / Wall , Track | |
| black , RAL 9005 ¹ | |
| IP20 | |
| 3610 lm | |
| optical inset 121 lm/W ² | |

LED

| | |
|---|--|
| 2700 K | |
| CRI ≥ 90 | |
| L80 / 50000 h | |
| initial MacAdam ≤ 3 SDCM | |
| R _g : 99 , R _r : 90 , R _{t(1-15)} : 88 | |
| MR 0.53 | |
| MDER 0.48 | |

Optical

| | |
|--------------------------|--|
| High Performance Opal | |
| opal (lambertsch) | |
| PstLM ≤ 1.0 ³ | |
| SVM ≤ 0.4 ³ | |

Electrical


| | |
|-----------------------|--|
| DALI-2 single control | |
| 48 V | |
| fixture 43 W | |
| optical inset 29.8 W | |
| PC3 | |
| 1 DALI Addr. | |

Physical

| | |
|----------------|--|
| length 2405 mm | |
| width 25 mm | |
| height 47 mm | |
| 1.5 kg | |

¹ RAL code ² incl. consideration of optical losses
³ Value of containing product at full load (undimmed)

Light distribution



Product drawing



Installation instructions

