

BO 45 base surface 1 lamp

049-6330538S



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Surface _____

tilt max 90° _____

rotation 350° _____

black , RAL9005 ¹ _____

IP20 _____

1110 lm _____

LED

3000 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 100 , R_f: 91 , R_{f(1-5)}: 88 _____

MR 0.59 _____

MDER 0.53 _____

Optical

spot _____

beam angle 12° _____

PstLM ≤ 1.0 ² _____

SVM ≤ 0.4 ² _____

Surface mounted spotlight made of aluminium; 1 lamp; cylindrical spotlight head; surface black powder coated; 350° rotatable and 90° tiltable; surface mounted housing in aluminium incl. converter; mounting plate with pre-assembled converter unit can be pre-mounted; luminaire housing can be attached without tools by interlock; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality, aluminium, vapour deposition coated reflector with faceted lens design; precise radiation characteristic with 12° beam; good glare control through recessed light point level; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC1 220-240V; incl. DALI-2 converter; flicker-free visual comfort through analogue current control (minimum value 1%); luminaire for through wiring; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Electrical

DALI-2 _____

15.0 W _____

PC1 220-240V _____

74 lm/W _____

1 DALI Addr. _____

Physical


length 180 mm _____

width 55 mm _____

height 163 mm _____


0.5 kg _____

Light distribution



spot 12°			
h (m)	E0° (lx)	ø (m)	
1	14000	0.21	
2	3500	0.42	
3	1600	0.63	
4	900	0.84	
5	600	1.06	

Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

