

BO 55 semi-recessed

049-6140518S 002-90726



Project / Type


Notes

Count / Date




Cylindrical spotlight in aluminium; surface black powder coated; 350° rotatable and 90° tiltable; recessed version with trim; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality, aluminium, vapour deposition coated reflector with faceted lens design; precise radiation characteristic with 17° beam; good glare control through recessed light point level; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC2; 220-240 V; incl. converter, non dimmable; external converter for ceiling insertion, through-wiring suitable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



spot 17°			
h (m)	EO° (lx)	ø (m)	
1	14700	0.30	
2	3700	0.59	
3	1600	0.89	
4	900	1.19	
5	600	1.48	

Product drawing



General

Ceiling Semi-Recessed
tilt max 90°
rotation 350°
black RAL 9005 ¹
IP20
1880 lm
fixture 89 lm/W ²

LED

3000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R _g : 100 R _f : 91 R _{f(1-15)} : 89
MR 0.59 MDER 0.53

Optical

spot beam angle 17°
PstLM ≤ 1.0 ³ SVM ≤ 0.4 ³

Electrical

non DIM
PC2 220-240 V
system 24.7 W fixture 21.0 W
36 Vf 600 mA

Physical

diameter 55 mm height 159 mm
0.45 kg

Cutout

diameter 46 mm
min. ceiling thickness 2 mm max. ceiling thickness 25 mm
recessed depth 190 mm

¹ RAL code
² incl. consideration of optical losses & internal control unit losses
³ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

