

# TULA micro suspended

canopy surface

049-5715514M 005-2602198



Project / Type

Notes

Count / Date



## General

Ceiling , Suspended  
chrome  
Canopy jet black  
IP20  
746 lm

## LED

3000 K  
CRI  $\geq 90$   
L90 / 50000 h  
initial MacAdam  $\leq 3$  SDCM  
 $R_g: 100, R_f: 90, R_{f(1-15)}: 87$   
MR 0.59  
MDER 0.54

## Optical

medium  
beam angle 25°

## Electrical


Casambi  
11.3 W  
PC2 220-240V  
66 lm/W

## Physical

diameter 47 mm  
height 500 mm

Decorative suspended luminaire in aluminium; surface polished chrome; pendant fitting with 1500mm suspension; incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 25° beam; degree of protection IP20; PC2 220-240V; light source not replaceable; control gear replaceable by an authorized professional;

## Light distribution



medium 25°

h (m)	EO° (lx)	ø (m)
1	3230	0.44
2	810	0.89
3	360	1.33
4	200	1.78
5	130	2.22

## Product drawing



## Installation instructions



## Lighting calculator

