

TULA nano suspended

canopy surface

049-5710414M 005-2602118



Project / Type


Notes

Count / Date



Decorative suspended luminaire in aluminium; surface polished chrome; pendant fitting with 1500mm suspension; incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 25° beam; degree of protection IP20; PC2; 220-240 V; light source not replaceable; control gear replaceable by an authorized professional;


Light distribution



medium 25°

h (m)	EO° (lx)	ø (m)
1	2620	0.44
2	660	0.89
3	290	1.33
4	160	1.77
5	100	2.22

Product drawing



General

Ceiling | Suspended

chrome

Canopy jet black

IP20

790 lm

fixture 89 lm/W ¹

LED

2700 K

CRI ≥ 90

initial MacAdam ≤ 2 SDCM

R_g: 97 | R_f: 91 | R_{f(1-15)}: 87

MR 0.52 | MDER 0.47

Optical

medium | beam angle 25°

Electrical

non DIM

PC2 | 220-240 V

system 11.8 W | fixture 8.9 W

18 Vf | 500 mA

Physical

diameter 26 mm | height 500 mm

0.41 kg

¹ incl. consideration of optical losses & internal control unit losses

Installation instructions



Lighting calculator

