

TULA micro suspended

canopy surface

049-5715418M 005-2602198



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Suspended _____
 black , RAL9005 ¹ _____
 Canopy jet black _____
 IP20 _____
 648 lm _____

LED

2700 K _____
 CRI ≥ 90 _____
 L90 / 50000 h _____
 initial MacAdam ≤ 3 SDCM _____
 R_g: 99 , R_r: 91 , R₍₁₋₁₅₎: 89 _____
 MR 0.54 _____
 MDER 0.49 _____

Optical

medium _____
 beam angle 25° _____

Electrical


Casambi _____
 11.3 W _____
 PC2 220-240V _____
 57 lm/W _____

Physical

diameter 47 mm _____
 height 500 mm _____

Decorative suspended luminaire in aluminium; surface black powder coated; pendant fitting with 1500mm suspension; incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 25° beam; degree of protection IP20; PC2 220-240V; light source not replaceable; control gear replaceable by an authorized professional;

Light distribution



medium 25°

h (m)	EO° (lx)	ø (m)
1	2800	0.44
2	700	0.89
3	310	1.33
4	180	1.78
5	110	2.22

Product drawing



¹ RAL code

Installation instructions



Lighting calculator

