

BO 45 semi-recessed

049-6130518M 002-90724



Project / Type

Notes

Count / Date




General
Ceiling , Semi-Recessed
tilt max 90°
rotation 350°
black , RAL9005 ¹
IP20
1290 lm

LED
3000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R _g : 100 , R _f : 91 , R _{f(1-5)} : 88
MR 0.59
MDER 0.53

Optical
medium
beam angle 24°
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Cylindrical spotlight in aluminium; surface black powder coated; 350° rotatable and 90° tiltable; recessed version with trim; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality, aluminium, vapour deposition coated reflector with faceted lens design; precise radiation characteristic with 24° beam; good glare control through recessed light point level; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC2 220-240V; incl. converter, non dimmable; external converter for ceiling insertion, through-wiring suitable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



medium 24°			
h (m)	EO° (lx)	ø (m)	
1	6210	0.43	
2	1550	0.86	
3	690	1.30	
4	390	1.73	
5	250	2.16	

Product drawing



Electrical
non DIM
15.9 W
PC2 220-240V
81 lm/W

Physical
diameter 45 mm
height 149 mm
0.39 kg

Cutout
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 160 mm

¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

