

TULA micro suspended

canopy trimless

049-5715417F 005-3511017 002-90732



Project / Type

Notes

Count / Date



General

Ceiling | Suspended

white | RAL 9016 ¹

Canopy traffic white

IP20

694 lm

LED

2700 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 99 | R_f: 91 | R_(f-15): 89

MR 0.54 | MDER 0.49

Optical

flood | beam angle 44°

PstLM ≤ 1.0^{2 3 4 5} | SVM ≤ 0.4^{2 3 4 5}

Electrical

non DIM

PC2 | 220-240 V

system 11.3 W | fixture 8.4 W

fixture 82 lm/W ⁶

18 Vf | 500 mA

Physical

diameter 47 mm | height 500 mm

1.04 kg

Cutout

diameter 65 mm

min. ceiling thickness 9 mm | max. ceiling

thickness 25 mm

recessed depth 70 mm

¹ RAL code ² wallwasher lens BO 45 007-1965780

³ oval lens BO 45 007-1965880 ⁴ soft lens BO 45 007-1965980

⁵ Value of containing product at full load (undimmed)

⁶ incl. consideration of optical losses & internal control unit losses


Installation instructions



Lighting calculator



Light distribution



flood 44°

h (m)	EO ³ (lx)	ø (m)
1	1290	0.82
2	320	1.64
3	140	2.45
4	80	3.27
5	50	4.09

Product drawing

