

# TULA nano suspended

canopy surface

049-551041XF 005-2602137



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

special colours

Canopy traffic white

IP20

674 lm

LED

2700 K

CRI ≥ 90

initial MacAdam ≤ 3 SDCM

Optical

flood

beam angle 30°

Electrical

DALI-2

12.0 W

PC2 220-240V

56 lm/W


Physical

diameter 26 mm

height 300 mm

Decorative suspended luminaire in aluminium; surface special colours powder coated; pendant fitting with 1500mm suspension; incl. feed (white), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 30° beam; degree of protection IP20; PC2 220-240V; light source not replaceable; control gear replaceable by an authorized professional;

## Light distribution



flood 30°

h (m)	EO° (lx)	ø (m)
1	1980	0.53
2	500	1.07
3	220	1.60
4	120	2.13
5	80	2.66

## Product drawing



Installation instructions

Lighting calculator

