

# BO 32 semi-recessed

049-612051XS 002-90742



Project / Type

Notes

Count / Date



220-240V

350°

X-PERT

X-PERT

General

Ceiling , Semi-Recessed

tilt max 90°

rotation 350°

special colours

IP20

800 lm

LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 91 , R<sub>f1-5</sub>: 88

MR 0.59

MDER 0.53

Optical

spot

beam angle 18°

PstLM ≤ 1.0 <sup>1</sup>

SVM ≤ 0.4 <sup>1</sup>

Electrical

non DIM

11.7 W

PC2 220-240V

68 lm/W

Physical

diameter 32 mm

height 139 mm

0.04 kg

Cutout


min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 60 mm


<sup>1</sup> Value of containing product at full load (undimmed)

## Light distribution



spot 18°			
h (m)	EO° (lx)	ø (m)	
1	6060	0.32	
2	1510	0.63	
3	670	0.95	
4	380	1.27	
5	240	1.58	

## Product drawing



Installation instructions

Lighting calculator



# BO 32 semi-recessed

049-612051XS 002-90742



Project / Type

Notes

Count / Date

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.92	0.88	0.85	0.81
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF <sup>a</sup>	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF <sup>a</sup>	Luminaire Maintenance Factor		LSF	Lamp Survival Faktor	

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	57
B13	75
B16	92
B20	115
C10	57
C13	75
C16	92
C20	115

## Components

### POWER SUPPLY

L-W-H (MM)	ARTICLE NUMBER(S)
65-39-20	002-90742



## Optional electrical accessories

### DIN RAIL POWER SUPPLY

L-W-H (MM)	ARTICLE NUMBER(S)
72-90-63	005-6520210



### DIN RAIL LED DRIVER

TYPE	L-W-H (MM)	ARTICLE NUMBER(S)
DALI-2   200-1050 mA   2 x 42W	36-88-59	005-6121030



## Optical accessories

### HONEYCOMB LOUVER

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
jet black	30	007-1965168

