

TULA nano suspended

canopy trimless

049-5510418F 005-3511017 002-90732



Project / Type

Notes

Count / Date



Decorative suspended luminaire in aluminium; surface black powder coated; pendant fitting with 1500mm suspension; incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 30° beam; degree of protection IP20; PC2 220-240V; canopy for trimless installation in plasterboard ceilings; suitable for ceiling thickness of 9-25 mm; special mounting tool for easy installation of the trimless housing available as an accessory; accessories are listed separately; incl. converter, non dimmable; external converter for ceiling insertion; light source not replaceable; control gear replaceable by an authorized professional;

Light distribution



flood 30°			
h (m)	EO° (lx)	ø (m)	
1	1980	0.53	
2	500	1.07	
3	220	1.60	
4	120	2.13	
5	80	2.66	

Product drawing



General

Ceiling , Suspended

black , RAL9005 ¹

Canopy traffic white

IP20

674 lm

LED

2700 K

CRI ≥ 90

initial MacAdam ≤ 3 SDCM

Optical

flood

beam angle 30°

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrical

non DIM

12.0 W

PC2 220-240V

56 lm/W

Physical

diameter 26 mm

height 300 mm

0.14 kg

Cutout

diameter 65 mm

min. ceiling thickness 9 mm

max. ceiling thickness 25 mm

recessed depth 70 mm

¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

